

A comparison study of discrete-ordinates and flux-limited-diffusion methods for modeling radiation transport

Eric S. Myra¹ and Wm. Daryl Hawkins²

¹University of Michigan

²Texas AM University

March 22, 2012

Abstract

The Center for Radiative Shock Hydrodynamics (CRASH) seeks to improve the predictive capability for models of Omega laser experiments of radiative shock waves. The laser is used to shock, ionize, and accelerate a beryllium plate into a xenon-filled shock tube. These shocks, when driven above a threshold velocity of about 60 km/s, become strongly radiative and convert most of the incoming energy flux into radiation.

Radiative shocks have properties that are significantly different from purely hydrodynamic shocks and, in modeling this phenomenon numerically, it is important to compute radiative effects accurately. In this presentation, we examine approaches to modeling radiation transport by comparing two methods: (i) a computationally efficient approximation (multigroup flux-limited diffusion), currently in use in the CRASH code, with (ii) a more accurate discrete-ordinates treatment that is offered by the code PDT. We present a selection of updated results from a suite of comparison tests, showing both idealized problems and those that are representative of conditions found in the CRASH experiment.

This research was supported by the DOE NSA/ASC under the Predictive Science Academic Alliance Program by grant number DEFC52-08NA28616.